

# BRIDGE FOR THE AIRBUS A-380 IN BARAJAS AIRPORT MADRID (SPAIN)

Prof. Dr. Carlos Jurado Cabañes  
Polytechnic University of Madrid  
Escuela de Ingeniería Técnica de Obras Públicas  
Dept. of Civil Engineering  
Spain  
[cjurado@ciccp.es](mailto:cjurado@ciccp.es)

## ABSTRACT

During the years 2004 and 2005 it has been constructed in Barajas airport of Madrid a special bridge for the new airplane AIRBUS A380. This new airplane has a weight of 1,500,000 pounds and 18 wheels with a reaction of 39.2 tonnes per each one and the braking force is about 600 tonnes. The enormous loads transmitted for the airplane made this bridge a special structure. The present article exposes the most important characteristics of project and construction, of one of the special bridges in the airport Barajas of Madrid. This bridge was constructed for the access to the hangar of airplanes in Barajas, known “La Muñoza”. The structure has a width of 48 m, two spans of 13 m each one and a vertical clearance of 5.50 m to allow passing vehicles under it, along the new motorway in Barajas (Madrid).

**KEYWORDS:** Aileron, Soil boring, Deck, Abutment, Sheet-pile, Pier-pile.

## 1 THE ENLARGEMENT OF THE AIRPORT OF BARAJAS

During the first decade on 21th century it has been made the enlargement of Barajas airport. The construction of four new airplane lanes will allow to reach a capacity of 120 movements per hour and to give service to 70 million passengers per year. The cost of this enlargement has reached more than 5 million Euros.

This includes the construction of two new airplane lanes, totaling four with the two existing ones, which will be parallel two by two. Also it has been planned to construct a new Terminal Area and his satellites buildings, which will be connected with the principal building by means of a rapid electric subterranean train or “people to move” (Fig. 1).

Besides the extension of air traffic in Barajas, for the construction and maintenance of airports the Airport National Agency (AENA) has considered necessary to enlarge the area of maintenance and repairing services known the hangar of “La Muñoza” one of the largest in the world.



Fig. nº 1 Enlargement of Barajas airport

The hangar of “La Muñoza” is located in the southeast of Barajas airport (figures 2 and 3)



Fig. nº 2 Aerial view of Barajas airport

In the hangar “La Muñoza” takes places for the planes, every five years the review D, known popularly as the Great Stop. A program of 100 % structural inspection for the airplane, which involves the total disassembly of it, the complete review, the repairing or the change of all the interior and exterior elements of the plane. For some 70 days, engines, landing gears, controls of flight, helms, ailerons, etc., that is, all the components of the airplane go out from his place, to be turning them to his place in perfect condition being this operation certified. The results of the maintenance are verified in land and even with a flight of test (Fig. 3).



Fig. nº 3 Hanga “La Muñoza” and the bridge of access to it.

## 2 THE NEW BRIDGE FOR THE AIRBUS A-380

The enlargement of Barajas airport includes the construction of an internal road highway of services and also the enlargement and amelioration of the hangar of “La Muñoza”. The highway for services in this area of Barajas airport is located between the runway 18-36 and the hangar of “La Muñoza”, so it has been necessary to construct a new bridge (Fig. 3) in order to locate the plane traffic above and the car traffic below.





## 5 THE CONSTRUCTION OF THE BRIDGE

The construction of the bridge must follow the next process (Fig. 8 and 9):

- First it must be prepared the soil to form an horizontal platform for the construction of piles
- Next it must construct the concrete piles of 1.25 m of diameter, separated 1.90 m from the centres.
- After, it must be constructed the beam to tie the heads of piles with  $b=2.10$  m and  $h = 1.60$  m on the abutments and the beam with trapezoidal transversal section on the central support.
- Once the sheet pile of abutments and the central piles has been constructed, it must be excavated the soil under the deck, for the motorway below the bridge.
- The next phase is to place the prestressed beams of 0.82 m height.
- After the beams have been put in place, the next phase is to spill the concrete to construct the compression slab over the prestressed beams.
- Finally it must construct the rest of the bridge.



Fig. nº 8 Construction of the bridge for the access to the hangar of “La Muñoza”



Fig. nº 9 Finished bridge

## 6 CONCLUSIONS

Finally it was constructed a new bridge with a width of 48 m and two spans of 15.375 and 13.375 m, and a vertical clearance of 5.50 m to allow passing vehicles under it, along the new motorway for the service of the airport of Barajas in Madrid and big airplanes over it.

The bridge now it is in service with satisfactory results. All types of airplanes have passed over it to the hangar of “La Muñoza”, but no one airplane was the Airbus A380, waiting for the decision to permit the landing of it.

## 7. REFERENCES

MOPU. *Spanish rules relative to the actions to consider in the project of railway bridges. IAPF-2007*

Ministry of Public Works. *Norm of seismic construction: General part and Building Construction. NCSE-O2*

Euro code 1.1. *Bases of project and actions in structure.*

Euro code 2. *Project of structures of reinforced concrete.*

Euro code 3. *Project of structures of steel.*

Jiménez Salas, *Geotecnia y Cimientos*. Ed. Rueda.

Jiménez Montoya, P., García Meseguer, A., Morán Cabré, F. *Hormigón armado*. 14th edition. Ed. Gustavo Gili.